


High Power LED E-Series

1W Amber

SPHAMTE1N1A0



Features

- Package : Ceramic package
- Dimension : 1.50 mm x 1.90 mm
- Chip Technology : Flip Chip
- ESD : 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM)
- Qualifications : AEC-Q102 Qualified with RV-level 0



Table of Contents

1.	Characteristics	-----	3
2.	Product Code Information	-----	4
3.	Typical Characteristics Graphs	-----	7
4.	Soldering Temperature Location	-----	12
5.	Mechanical Dimension	-----	13
6.	Soldering Conditions	-----	14
7.	Tape & Reel	-----	15
8.	Label Structure	-----	16
9.	Packing Structure	-----	17
10.	Precautions in Handling & Use	-----	18
11.	Company Information	-----	19

1. Characteristics

a) Typical Characteristics ($T_s = 25^\circ\text{C}$)^[1]

Item	Symbol	Value	Unit.
Chromaticity Coordinate	Cx Cy	0.57 0.42	
Luminous Flux ($I_F = 350\text{ mA}$)	Φ_V	Typ. 110	lm
Forward Voltage ($I_F = 350\text{ mA}$)	V_F	Typ. 3.0	V
Viewing Angle	Φ	Typ. 120	°
Reverse Current	I_R	Not designed for reverse operation	
Real Thermal Resistance (Junction to Solder point)	$R_{th_J-S (Real)}$	Typ. 5.4 Max. 5.8	K/W
Electrical Thermal Resistance (Junction to Solder point)	$R_{th_J-S (Elec.)}$	Typ. 3.8 Max. 4.1	K/W
Radiant Surface	A	1.10	mm ²

Note:

[1] The measurement condition means that temperature dependence is excluded by applying pulse current for typically 25ms.

b) Absolute Maximum Rating

Item	Symbol	Rating	Unit
Ambient / Operating Temperature	T_a	-40 ~ +125	°C
Storage Temperature	T_{stg}	-40 ~ +125	°C
LED Junction Temperature	T_j	150	°C
Maximum Forward current ^[2] ($T_s: 25^\circ\text{C}$) ^[3]	I_F	800	mA
Minimum Forward current ^[2] ($T_s: 25^\circ\text{C}$) ^[3]	I_F	50	mA
Maximum Reverse current		Do not apply for reverse current	
ESD Sensitivity ^[4]	-	±8 for HBM	kV

Note:

[2] Driving the product at forward current (I_F) below Min. I_F or above Max. I_F may result in unpredictable behavior of the product.

[3] The measurement condition means that temperature dependence is excluded by applying pulse current for typically 25 ms

[4] It is included the device to protect the product from ESD.

2. Product Code Information

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
S	P	H	A	M	T	E	1	N	1	A	0	A	B	C	D	E	F

Digit	PKG Information
1 2	Company name and Samsung LED PKG (SP for Samsung PKG)
3	Power variant (H for automotive high power)
4 5	Color variant (AM for automotive amber color)
6	LED PKG version (T for first version up)
7 8	Product configuration and type (E1 for automotive E-Series PKG type)
9	Lens configuration (N for no lens)
10	Typical power (1 for 1±0.5W)
11	Special internal code (A for automotive version)
12	Specific property (0 for default)
13 14	Forward voltage property
15 16	CIE coordination property
17 18	Luminous flux property

a) Luminous Flux Bins ^[5] ($I_F = 350 \text{ mA}$, $T_S = 25^\circ\text{C}$)

Symbol	Flux Bin Code	Flux Range (lm)	
		Min	Max
Φ_V	K1	100	110
	N1	110	120

a) Voltage Bins ^[5] ($I_F = 350 \text{ mA}$, $T_S = 25^\circ\text{C}$)

Symbol	Voltage Bin Code	Voltage Range (V)	
		Min	Max
V_F	1D	2.75	3.00
	1E	3.00	3.25

Note:

[5] Luminous flux measuring equipment: CAS140CT

Φ_V and V_F tolerances are $\pm 7\%$ and $\pm 0.1\text{V}$, respectively.



c) Color Bin ^[6](I_F = 350 mA)

Symbol	Color Bin Code	Cx				Cy			
Cx, Cy	A1	0.5606	0.5705	0.5883	0.5780	0.4250	0.4289	0.4111	0.4080

Note

[6] Luminous flux measuring equipment: CAS140CT


Chromaticity coordinates: Cx, Cy according to CIE 1931. Cx and Cy tolerances are ±0.005, respectively.


d) Luminous Flux Bins according to Color Bin (I_F = 350 mA, T_s = 25 °C)

Symbol	Flux Bin Code	Flux Range (lm)			
		K1		N1	
		Min	Max	Min	Max
		100	110	110	120
Φ _v	A1	O		O	


3. Typical Characteristics Graphs

a) Spectrum Distribution ($I_F = 350 \text{ mA}$, $T_S = 25 \text{ }^\circ\text{C}$)






Note: The UV radiation of the light (250~400nm) $\leq 10^{-5} \text{ W/lm}$ according to ECE regulation

b) Typical Chromaticity Coordinate Shift vs Radiation Angle ($I_F = 350 \text{ mA}$, $T_S = 25 \text{ }^\circ\text{C}$) [7]



Note: [7] The measurement condition means that temperature dependence is excluded by applying pulse current for typically 25ms




c) Forward Current Characteristics ($T_s = 25\text{ }^{\circ}\text{C}$)^[8]




Note:

[8] The measurement condition means that temperature dependence is excluded by applying pulse current for typically 25 ms

d) Temperature Characteristics ($I_F = 350 \text{ mA}$)




e) Derating Curve ^[9]




Note:

[9] The measurement condition means that temperature dependence is excluded by applying pulse current for typically 25 ms


f) Permissible Pulse Handling Capacity ($I_F = f(t_p)$; D: Duty cycle, $T_s = 125^\circ\text{C}$)



g) Beam Angle Characteristics ($I_F = 350 \text{ mA}$, $T_S = 25 \text{ }^\circ\text{C}$)



4. Soldering Temperature Location




T_j : Temperature of Junction

T_s : Temperature of Solder Pad

R_{thJS} : Thermal Resistance from Junction to Solder Pad

5. Mechanical Dimension



[Top view]

[Side view]

[Bottom view]

Note:

The dimensions in parentheses are for reference purposes.

Unit: mm, Tolerance: ± 0.1 mm


Approximate weight : 6.5mg

a) Pick and Place

Do not place pressure on the resin molded part

It is recommended to use a pick & place nozzle CN065, etc.

b) Electric Schematic Diagram




c) Material Information

Description	Material
Substrate	Ceramic Substrate
LED Die	Flip Chip
Phosphor sheet	Silicone
Zener Diode	Silicone
Wire	Au
Resin Mold	Silicone

6. Soldering Conditions

a) Pad Configuration




Notes:

Unit : mm, Tolerance : ± 0.10 mm

b) Reflow Conditions (Pb free)

Reflow frequency: 2 times max.




※ All temperature refer to the pad of package.

c) Manual Soldering Conditions

Not more than 5 seconds @ max. 300 °C, under soldering iron.(one time only)

8. Label Structure

a) Label Structure




Note: Denoted bin code and product code above is only an example (see description on page 5)

Bin Code:

- Ⓐ Ⓑ: Forward Voltage bin (refer to page 5)
- Ⓒ Ⓓ: Chromaticity bin (refer to page 6)
- Ⓔ Ⓕ: Luminous Flux bin (refer to page 5)

b) Lot Number

The lot number is composed of the following characters:




① ②③③②③④⑤⑥⑦⑧⑨ / 1ⒶⒷⒸ / 3,000 pcs

① ②	: Production site (SL : Kiheung, GA : Tienjin)
③	: Product state (A: Normal, B: Bulk, C: First Production, R: Reproduction, S: Sample)
④	: Year (G: 2022, H: 2023, I: 2024...)
⑤	: Month (1~9, A, B, C)
⑥	: Day (1~9, A, B~V)
⑦⑧⑨	: Serial number (001 ~ 999)
ⒶⒷⒸ	: Product serial number (001 ~ 999)

9. Packing Structure

a) Packing Process (The quantity of PKG on the Reel to be Max 3,000pcs)



Dimension of Transportation Box in mm

Width	Length	Height
220	245	182

10. Precautions in Handling & Use

- 1) For over-current protection, we recommend the use of resistors to prevent sudden current surges caused by slight shifts in voltage.
- 2) LEDs should not be contacted to any type of fluid (i.e. water, oil, organic solvent, etc.). If cleaning is required, only use isopropyl alcohol.
- 3) The maximum ambient temperature must be considered in order for the maximum temperature ratings not to be exceeded.
- 4) LEDs must be stored in a clean environment. If the LEDs are to be stored for 3 months or more after being shipped from Samsung Electronics, they should be packed by a sealed container with nitrogen gas injected. (Shelf life of sealed bags: 12 months, temp. $\sim 40^{\circ}\text{C}$, $\sim 90\%$ RH)
- 5) After storage bag is open, LED subjected to soldering, solder reflow, or other high temperature processes must be:
 - a) Mounted within 672 hours (28 days) at an assembly line with a condition of no more than 30°C / 60% RH.
 - b) Stored at $<10\%$ RH.
- 6) Repack unused products using anti-moisture packing, fold to close any openings and store in a dry place with $<10\%$ RH
- 7) LEDs require baking before mounting, if humidity card reading is $>60\%$ at $23\pm 5^{\circ}\text{C}$.
- 8) If baking is required, LEDs must be baked for 1 day at $60\pm 5^{\circ}\text{C}$.
- 9) LEDs are sensitive to electrostatic discharge and surges. Applying any voltage exceeding the absolute maximum rating of the LED can cause permanent damage to the device. Damaged LEDs may have some unusual characteristics such as increased leakage current, lower turn-on voltage or may light abnormally at low current. When handling LEDs, using grounding wrist-bands or anti-static gloves is recommended.
- 10) VOCs (volatile organic compounds) present in adhesives, flux, hardeners or organic additives, etc. that are used in luminaires may lead to discoloration of the LED when exposed to heat or light. Note that VOCs can permeate silicone bags. This phenomenon can significantly affect light output from the luminaire. To avoid this issue, please carefully evaluate materials used in your process and/or luminaire to be free of VOCs.

11. Company Information

SAMSUNG

Copyright @1995-2024 All rights reserved

Samsung Electronics LED BUSINESS

1, Samsung-ro Giheung-gu
Yongin-si, Gyeonggi-do 17113 Korea

<http://www.samsung.com/led>

Sales Contact

leedw007@samsung.com

jh0932.yang@samsung.com

US

Samsung Semiconductor, Inc.
11800 Amber park Drive #225 Alpharetta, GA 30004 USA
Tel : +1 678 892 7385

Europe

Samsung Semiconductor Europe GmbH,
Einsteinstrasse 174, 81677 Munich, Germany
Tel : +49 6196 66 3902

Japan

Samsung Japan Corporation
10F, Shinagawa Grand Central Tower 2-16-4, Kounan, Minato-ku, Tokyo
108-8240, Japan
Tel : +81 3 6369 6267

China(Shenzhen)

Samsung Electronics Co., Ltd.
25F/26F, SCC building A, No.88, Haide Yi Road, Nanshan District,
518026, Shenzhen China
Tel : +86 21 2325 3551

China(Shanghai)

Samsung Electronics Co., Ltd.
Building B, No 1065 Zhongshan RD(W), Changning District, Shanghai,
China
Tel : +86 21 2325 3504

India

Samsung Electronics
Suite #006 Ground Floor, Copia Corporate Suites, Jasola, New Delhi
110025, India, Delhi, IND
Tel : +91 9600003320

SAMSUNG

Legal and additional information.

[About Samsung Electronics Co., Ltd.](#)

Samsung inspires the world and shapes the future with transformative ideas and technologies.

The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, network systems, and memory, system LSI, foundry and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Copyright © 2024 Samsung Electronics Co., Ltd. All rights reserved.

Samsung is a registered trademark of Samsung Electronics Co., Ltd.

Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

1, Samsung-ro

Giheung-gu

Yongin-si, Gyeonggi-do, 446-711

KOREA

www.samsung.com/led

The Samsung logo, consisting of the word "SAMSUNG" in a bold, blue, sans-serif typeface.